

3P 4G

6kW

4G NEW

Solis 3P 4G Three Phase Inverter

- ▶ Solis 4G Three Phase Range
- ▶ 160V-850V MPPT voltage range-ultra low startup
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ THDi<1.5%, low harmonic distortion against grid
- ▶ Over 98.7% Max.efficiency
- ▶ RS485, WiFi/LAN/GPRS (optional) interface
- ▶ Multiple protections levels
- ▶ WiFi monitoring available-iphone and android app available
- ▶ 5 years standard warranty, 20 years optional upgrade



Model:

400V Solis-3P6K-4G

Features:

THDi
—
<1.5%

IP65

160-850
—
MPPT voltage range

AFCI
—
Optional

WiFi/GPRS
—
Real time monitoring

Available on the iPhone
App Store
—
Available on the Android
App Store

Datasheet

| Model | Solis-3P6K-4G |
|--------------------------------------|---|
| Energy Source | PV |
| Input Side(DC) | |
| Max. DC input power(kW) | 7.2 |
| Max. DC input voltage(V) | 1000 |
| Start-up voltage(V) | 180 |
| MPPT voltage range(V) | 160-850 |
| Max. input current per MPPT(A/B) | 11A+11A |
| MPPT number/Max input strings number | 2 / 2 |
| Output Side (AC) | |
| Rated output power(kW) | 6 |
| Max. apparent output power(kVA) | 6.6 |
| Max. output power(kW) | 6.6 |
| Rated grid voltage(V_{LL}) | 400 |
| Rated grid frequency(Hz) | 50/60 |
| Operation phase | Three |
| Rated grid output current@400V | 8.7 |
| Max. output current(A) | 9.5 |
| Power Factor (at rated output power) | 0.8 leading ... 0.8 lagging |
| THDI (at rated output power) | <1.5% |
| DC injection current | <0.5%In |
| Grid frequency range(Hz) | 47-52 or 57-62 |
| Efficiency | |
| Max.efficiency | 98.3% |
| EU efficiency | 97.8% |
| MPPT efficiency | >99.5% |
| Protection | |
| DC reverse-polarity protection | Yes |
| Short circuit protection | Yes |
| Output over current protection | Yes |
| Output over voltage protection | Yes |
| Insulation resistance monitoring | Yes |
| Residual current detection | Yes |
| Surge protection | Yes |
| Islanding protection | Yes |
| Temperature protection | Yes |
| Integrated DC switch | Yes |
| General Data | |
| Dimensions(mm) | 310W*538H*158D |
| Weight(kg) | 13.6 |
| Topology | Transformerless |
| Self consumption (night) | <1W(Night) |
| Operating ambient temperature range | -25~60°C |
| Ingress protection | IP65 |
| Noise emission{typical} | <30 dBA |
| Cooling concept | Natural convection |
| Max.operation altitude | 4000m |
| Designed lifetime | >20 years |
| Grid connection standard | EN50438, G59/3, AS4777, VDE0126-1-1, IEC61727 |
| Relative humidity | 0~100% |
| Safety/EMC standard | IEC62109-1/-2, AS3100 |
| Features | |
| DC connection | MC-4 mateable |
| AC connection | Terminal connectors |
| Display | LCD,2×20 Z. |
| Communication connections | 4 pins RS485 connector |
| Warranty | 5 years standard (extend to 20 years) |