

InfiniSolar WP 30kW



- IP65 waterproof and dustproof makes the inverter available for various working conditions.
- 150% unbalanced load support
- Dual outputs for smart load management
- Built-in AC coupled function
- Built-in WiFi for mobile monitoring (App is available)
- User-adjustable charging current up to 50A
- Wide battery input range
- Built-in communication port for BMS (RS485)
- Parallel operation up to 4 units

InfiniSolar WP Three Phase On-Grid Inverter with Energy Storage Specification

MODEL	InfiniSolar WP 30KW
MAXIMUM PV INPUT POWER	40000 W
RATED OUTPUT POWER	30000 W
MAXIMUM CHARGING POWER	18000 W
GRID-TIE OPERATION	
PV INPUT (DC)	
Nominal DC Voltage / Maximum DC Voltage	720 VDC / 1000 VDC
Start-up Voltage / Initial Feeding Voltage	320 VDC / 350 VDC
MPP Voltage Range	350 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	3 / A: 26A, B: 26A, C: 26A
Number of Strings Per MPP Tracker	A: 2, B: 2, C: 2
GRID/UTILITY OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Output Voltage Range	184 - 265 VAC per phase
Nominal Output Current	43.5 A per phase
Power Factor	0.9 lag to 0.9 lead
EFFICIENCY	
Maximum Conversion Efficiency (DC/AC)	96.5%
European Efficiency@ Vnominal	96%
OFF-GRID OPERATION	
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC per phase
Acceptable Input Voltage Range	170 - 280 VAC per phase
Maximum AC Input Current	50 A
PV INPUT (DC)	
Maximum DC Voltage	1000 VDC
MPP Voltage Range	350 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	3 / A: 26A, B: 26A, C: 26A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Output Waveform	Pure sine wave
Efficiency (DC to AC)	96%
HYBRID OPERATION	
PV INPUT (DC)	
Maximum DC Voltage	1000 VDC
Start-up Voltage / Initial Feeding Voltage	320 VDC / 350 VDC
MPP Voltage Range	350 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	3 / A: 26A, B: 26A, C: 26A
GRID OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Output Voltage Range	184 - 265 VAC per phase
Nominal Output Current	43.5 A per phase
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	120 - 140 VAC / 180 VAC per phase
Acceptable Input Voltage Range	170 - 280 VAC per phase
Maximum AC Input Current	50 A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Efficiency (DC to AC)	96%
BATTERY & CHARGER	
Battery Voltage Range	600 ~ 1000 VDC
Maximum Charging Current	30 A
GENERAL	
PHYSICAL	
Dimension, D x W x H (mm)	255 x 660 x 750
Net Weight (kgs)	73
INTERFACE	
Communication Port	RS-232, USB, DRY CONTACT, RS-485 and Wi-Fi
Intelligent Slot	Optional SNMP, MODBUS and GPRS
ENVIRONMENT	
Humidity	0 ~ 100% RH
Operating Temperature	-25°C to 60°C (>45°C De-rating)
Altitude	0 ~ 1000 m**

*These figures are based on VDE-4105 standard. All figures may vary depending on different AC voltage and country requirements.

** Power derating 1% every 100 m when altitude is over 1000m
Product specifications are subject to change without further notice.