

Axpert VM II Premium Off-Grid Inverter



Axpert VM II Premium 1.2K,
Axpert VM II Premium 2.5K,
Axpert VM II Premium 3K-48V

Axpert VM II Premium 3K-24V

Axpert VM II Premium 5K

- Pure sine wave solar inverter
- Reserved communication port for BMS
- Wide PV input range, starts from 30VDC for 1.2K/2.5K/3K-24V models
- Battery independent design
- Maximum charging current 100A
- Battery equalization function to optimize battery performance and extend lifecycle
- Built-in anti-dust kit

Axpert VM II Premium Off-Grid Inverter Selection Guide

MODEL	Axpert VM II Premium 1.2K	Axpert VM II Premium 2.5K	Axpert VM II Premium 3K-24V	Axpert VM II Premium 3K-48V	Axpert VM II Premium 5K
Rated Power	1200VA/1200W	2500VA/2500W	3000VA/3000W	3000VA/3000W	5000VA/5000W
INPUT					
Voltage	230 VAC				
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)				
Frequency Range	50 Hz/60 Hz (Auto sensing)				
OUTPUT					
AC Voltage Regulation (Batt. Mode)	230VAC ± 5%				
Surge Power	2400VA	5000VA	6000VA	6000VA	10000VA
Efficiency (Peak)	93%				
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)				
Waveform	Pure sine wave				
BATTERY					
Battery Voltage	12 VDC	24 VDC		48 VDC	
Floating Charge Voltage	13.5 VDC	27 VDC		54 VDC	
Overcharge Protection	16 VDC	32 VDC		63 VDC	
SOLAR CHARGER & AC CHARGER					
Solar Charger Type	MPPT				
Maximum PV Array Open Circuit Voltage	350 VDC	450 VDC			500 VDC
Maximum PV Array Power	2000W	3000W			5000W
Maximum PV Input Current	13A				18A
MPP Range @ Operating Voltage	30 ~ 300 VDC (30 ~ 60VDC with battery connected)	30 ~ 400 VDC (30 ~ 60VDC with battery connected)		60 ~ 400 VDC	120 ~ 450VDC
Maximum Solar Charge Current	100 A				100A
Maximum AC Charge Current	80A			60A	100A
Maximum Charge Current	100A				100A
PHYSICAL					
Dimension, D x W x H (mm)	90 x 288 x 357		110 x 288 x 390	90 x 288 x 357	120 x 300 x 440
Net Weight (kgs)	6.5	7.0	7.2	7.0	10
Communication Interface	RS232/RS485, optional WiFi				
ENVIRONMENT					
Humidity	5% to 95% Relative Humidity (Non-condensing)				
Operating Temperature	-10°C to 50°C				
Storage Temperature	-15°C to 60°C				

Product specifications are subject to change without further notice.